

Tarpaulin welding machine

# TARPON

Compact,  
handy,  
innovative

- for welding of coated fabrics, foils and tarps
- digital display showing speed, temperature and air flow
- automatic drive start system
- high welding speed
- wrinkle-free welding
- new design and new technology



Due to more air flow higher welding speed.  
Available for 20, 30 or 40 mm width welding seam.

#### Technical data

|                      |       |                    |
|----------------------|-------|--------------------|
| Voltage              | V     | 230                |
| Frequency            | Hz    | 50/60              |
| Power consumption    | W     | 2300/2900          |
| Temperature          | °C    | 20-620             |
| Speed                | m/min | 0,5-12             |
| Air flow max. (20°C) | l/min | 500                |
| Air flow             | %     | 50-100 variable    |
| Noise level          | dB    | 50                 |
| Size (l x w x h)     | mm    | 410 x 260 x 200    |
| Weight               | kg    | 11,5 with 5 m cord |
| Protection class I   |       | ⊕                  |

Available on request  
with 120 V.

Version with integrated  
ATC (Automatic-Track-  
Control) for running by  
itself at the edge of the  
overlap. Available on  
request.

**BAK**  
www.bak-ag.com

BAK Thermoplastic  
Welding Technology AG  
Birkhoferweg 5  
6056 Kägiswil/Switzerland

E-Mail [info@bak-ag.com](mailto:info@bak-ag.com)

Telefon +41 (0)41 661 22 56

Fax +41 (0)41 661 22 51